



Best. Nr.	B [mm]	Anzahl Achsen	Scherenwangen	Rollen pro Achse	Anzahl Füße	T min [mm]	T max [mm]	L min [mm]	L max [mm]	Tragfähigkeit zwischen 2 Füßen [daN]	Fördergeschwindigkeit [m/s]	Stromversorgung
1350 413 SV	400		2	1	3	56	150	1900	4500	30	0,3	1x230V 50 Hz
1350 414 SV			2	1	4	56	150	2500	6300	30	0,3	1x230V 50 Hz
1350 415 SV			2	1	5	56	150	3100	8000	30	0,3	1x230V 50 Hz
1350 513 SV	500		2	1	3	56	150	1900	4500	30	0,3	1x230V 50 Hz
1350 514 SV			2	1	4	56	150	2500	6300	30	0,3	1x230V 50 Hz
1350 515 SV			2	1	5	56	150	3100	8000	30	0,3	1x230V 50 Hz
1350 613 SV	600		2	1	3	56	150	1900	4500	30	0,3	1x230V 50 Hz
1350 614 SV			2	1	4	56	150	2500	6300	30	0,3	1x230V 50 Hz
1350 615 SV			2	1	5	56	150	3100	8000	30	0,3	1x230V 50 Hz